

**WARNING**

DESIGN ENGINEERS, TECHNICIANS & INSTALLERS


THE INLET AND OUTLET OF THE ROTARY VALVE MUST HAVE PROPER ATTACHMENTS TO PREVENT ANYONE FROM BEING ABLE TO INSERT THEIR HANDS OR ANY OTHER BODY PARTS INTO THE VALVE WHEN IN OPERATION.

DETAIL NO.	NO. REQ.	DESCRIPTION
11	12	3/8-16X2 1/2 PLATED HEX BOLT
10	12	3/8 PLATED SPRING LOCK WASHER
9	4	1/4 SAE PLATED FLAT WASHER
8	4	3/8-16X2.0 FULL DOG SOCHD SETSC
7	4	3/8-16 PLATED HEX JAM NUT
6	2	ER-30 BEARX
5	2	PACKING GLAND PLATE
4	54	3/8" SQ PACKING RINGS
3	1	WF394 ROTOR
2	2	WF394 END PLATE
1	1	WF394 CYLINDER

- NOTES:**
- THIS FEEDER IS A PRECISION PIECE OF EQUIPMENT WITH CLOSE INTERNAL CLEARANCES. DO NOT CAUSE MISALIGNMENT BY BOLTING DOWN TO AN UNEVEN SURFACE, OR BY STRUCTURALLY PUTTING THE FEEDER IN A STRAIN.
  - BEARINGS ARE LIFETIME LUBRICATED.

CUSTOMER \_\_\_\_\_  
 CUST. P.O. NO. \_\_\_\_\_  
 SMOOT JOB NO. \_\_\_\_\_  
 ITEM NO. \_\_\_\_\_  
 QTY. \_\_\_\_\_  
 DRAWING ISSUE \_\_\_\_\_

OF #10.19-6-A  
 REV. 0 07/24/92  
 PAGE 1 OF 1



**MAGNUM**  
S Y S T E M S

1250 Seminary St.  
 Kansas City, KS 66103  
 Toll Free: 800.746.7000  
 Fax: 913.582.7883

2205 Johti Avenue  
 Parsons, KS 67357  
 Toll Free: 888.882.9567  
 Fax: 620.421.5586

**WF394 FEEDER ASSEMBLY  
 CUSTOMER DRAWING**

DATE	07/24/92	DWG. NO.	39-2
DWG. BY	JLG	APPROVED	
SCALE	NONE		